



济南迈科管道科技有限公司
质量证明书

Jinan Mech Piping Technology Co.,Ltd.
Certificate of Quality

EN 10204 3.1

产品名称: 涂塑钢管

Products Description: Red Epoxy Pipes

收货单位:CO002293

Purchaser:CO002293

合同号: B10-232E370B-JG

Contract No:B10-232E370B-JG

下列产品在 ISO 9001 质量管理体系监督下组织生产, 在严格按照与贵公司所订合同中规定之技术要求进行检验后, 特发此质量证明书。

This is to certify that the products listed here have been manufactured and checked strictly according to technical standards and requirements set forth in the contract.And our production is carried out under the supervision of ISO 9001 Quality Management System.

质保书编号: 20240118001

No:20240118001

标准: ASTM A795

Standard: ASTM A795

发货日期: 2024. 1. 18

Delivery Date:2024.1.18

序号	批 号	规格 (mm) Dimension 外径 × 长度 O.D × L	化 学 成 份 (%) Chemical Composition											屈服强度 Yield Strength Rel (MPa)	抗拉强度 Tensile Strength Rm (MPa)	延伸率 Elongation A (%)	冲击试验 Impact Test		
			碳	硅	锰	磷	硫	铬	镍	铜	铝	钛	铌				温度℃	横向	纵向
No.	Batch No.		C	Si	Mn	P	S	Cr	Ni	Cu	Al	Ti	Nb						
1	21692D1506	RPGG 11/4X5800MM	0,07	0,12	0,36	0,013	0,014	—	—	—	—	—	—	343	419	32	—	—	—
2	85216CZA06	RPGG 11/2X5800MM	0,09	0,14	0,32	0,018	0,015	—	—	—	—	—	—	326	443	31	—	—	—
3	35395CYY10	RPGG 2X5800MM	0,09	0,14	0,34	0,015	0,013	—	—	—	—	—	—	337	426	33	—	—	—
4	45246CZM11	RPGG 21/2X5800MM	0,07	0,12	0,33	0,019	0,016	—	—	—	—	—	—	354	447	31	—	—	—
5	85614CZH08	RPGG 4X5800MM	0,06	0,15	0,35	0,014	0,012	—	—	—	—	—	—	341	431	33	—	—	—
6	45342CZT07	RPGG 6X5800MM	0,08	0,13	0,33	0,022	0,017	—	—	—	—	—	—	322	417	32	—	—	—

No.	规格 (mm) Dimension 外径 × 长度 O.D × L	数量 Quantity			水压试验 Hydrostatic Test MPa (5s)	无损检验 涡流探伤 E .T.	压槽或螺 纹检验 Grooved/Threaded	外观检 测 Outlook inspection	冷弯或压扁 Cold Bending or Flattening	镀锌均匀性(次) Galv. Surface Uniformity	平均镀锌层重量(g/m²) Ave. Mass of Galv.
		件 数 Bundles	支 数 Piece	重量(kg) Weight (kg)							
1	RPGG 11/4X5800MM	10	610	9.517,22	6,89	OK	OK	OK	OK	—	—
2	RPGG 11/2X5800MM	1	61	1.100,32	6,89	OK	OK	OK	OK	—	—
3	RPGG 2X5800MM	3	111	2.530,13	6,89	OK	OK	OK	OK	—	—
4	RPGG 21/2X5800MM	18	342	10.433,74	6,89	OK	OK	OK	OK	—	—
5	RPGG 4X5800MM	7	133	6.456,62	8,27	OK	OK	OK	OK	—	—
6	RPGG 6X5800MM	4	28	2.245,99	6,89	OK	OK	OK	OK	—	—

备注: 管端类型: P代表平端; N代表螺纹; PG代表压槽; NSC代表接箍。

Remarks: P:Plain End; N:Threaded End; PG: Grooved End; NSC: Threaded and socket one end

注: 用户若查询产品质量, 请将产品钢级、熔炼号、批号、证书编号、发货日期、合同号等写入函内。

Note: If there is any question with quality, please offer the steel grade, heat NO., lot NO., certificate NO., contract NO., ETC.

检验员: 赵书鹏

Inspect: Zhao Shupeng

审核: 刘鲁佳

Auditor: Liu Lujia

签批: 刘鲁佳

Approval: Liu Lujia

联系电话(Tel): 0531-87601999

传 真(Fax): 0531-87666796

