




# SWAY BRACE COMPONENTS

## SSB0303 – Quick Bracing Clamp

- **Function:** Braces pipe against sway or seismic disturbance. Provides an easy lateral connection joining brace member and pipe together as a complete assembly.
- **Size:** Braces pipe from 1” to 6”.
- **Finish:** Zinc plated. Other finishes upon request.
- **Material:** Carbon steel
- **Installation:** Place over the pipe to be braced, and insert brace member through opening leaving a minimum 1” extending from attachment. Must leave a minimum of 6” away from a pipe joint.
- **Qualification:** Comply with NFPA 13 and UL listed form 1” ~ 4”



### Dimensions

Pipe Size	R	L	Brace Member	Max. Design Load
in	mm	mm		lbs. (kN)
1	17.5	52	1" SCH40 Pipe	680 (3.02)
1 1/4	22	60	1" SCH40 Pipe	680 (3.02)
1 1/2	25	66	1" SCH40 Pipe	680 (3.02)
2	31	79	1" SCH40 Pipe	680 (3.02)
2 1/2	39	95	1" SCH40 Pipe	680 (3.02)
3	46	107	1" SCH40 Pipe	680 (3.02)
4	59	132	1" SCH40 Pipe	680 (3.02)
*5	71	158	1" SCH40 Pipe	1090 (4.85)
*6	85	187	1" SCH40 Pipe	1090 (4.85)

\* No UL Listed.