

PROMASEAL®-A Fire stopping acrylic



General description

PROMASTOP®-A is an acrylic-based, single component fire stopping sealant. Joints without movement can be sealed quickly and securely thanks to its outstanding application qualities. A common emulsion paint can be used to colour the joints.

Field of application

PROMASTOP®-A is a fire stopping sealant for joints in walls and floors with a maximum movement of 7.5%.

PROMASEAL-A can also be used as an annular clearance seal between structural components and sustained insulation.

System advantage / customer benefit

- Can be painted
- Good adhesion to various substrates

Test certificate / approval

- EN 1366-3/4
- EN 13501-1/2
- ETAG 026-2

Packaging

- 310 ml cartridges
- 12 cartridges/box
- 1200 cartridges/palett

Subject to change

Storage requirements

- Store in cool and dry conditions: 3°C - 35 °C
- Shelf life of original sealed containers at least 12 months
- Once opened, containers should be finished swiftly

Safety instructions

- Please refer to the safety data sheet for additional advice

Technical Data and Properties

Colour	white/grey
Consistency	paste
Density	wet : $1.6 \pm 0.2 \text{ g/cm}^3$ dry : $1.8 \pm 0.2 \text{ g/cm}^3$
Solid Content	$86 \pm 5 \text{ wt\%}$
Movement Capabilities	elongation minimum 15% compression minimum 15%
Use category	Class Y1
Reaction to fire	Class E